

2009

- Avramidis, G.; Wolkenhauer, A.; Zhen, B.; Militz, H.; Viöl, W.: Water-Repellent Coatings on Wood Surfaces Generated by a Dielectric Barrier Discharge Plasma Jet at Atmospheric Pressure. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 269-275
- Dieste A, Krause A, Bollmus S, Militz H (2009) Gluing ability of plywood produced with DMDHEU-modified veneers of *Fagus sp.*, *Betula sp.* and *Picea sp.* J ADHESION, 29: 206-209
- Dieste A, Krause A, Mai C, Sèbe G, Grelier S, Militz H (2009) Modification of *Fagus sylvatica* (L.) with 1,3-dimethylol-4,5-dihydroxyethylene urea (DMDHEU). Part 2: Pore size distribution determined by differential scanning calorimetry. HOLZFORSCHUNG, 63 (1): 89-93
- Dieste, A.; Krause, A.; Mai, C.; Militz, H.: The Determination of EMC and its Effect on the Analysis of Moisture Sorption in Wood Modified with DMDHEU. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 85-91
- Ghosh, S. C.; Militz, H.; Mai, C.: Natural Weathering of Scots Pine (*Pinus sylvestris* L.) Wood Modified by Functionalized Commercial Silicone Emulsions. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 253-260
- Grüneberg T, Mai C, Militz H, Radovanovic I, Kretschmer K, Kurda K (2009) Holz und Kunststoff - die Eigenschaften der Rohstoffe für Wood Plastic Composites (WPC). Holztechnologie, 50 (2): 37-40
- Grüneberg T, Mai C, Militz H, Radovanovic I, Kretschmer K, Kurda K (2009) Holz und Kunststoff - die Eigenschaften der Rohstoffe für Wood Plastic Composites (WPC). Teil 2. Holztechnologie, 50 (3): 28-31
- Grüneberg, T.; Krause, A.; Mai, C.; Militz, H.: Improvement of Interfacial Bonding of WPC Based on Various Maleic Acid Anhydride Pre-treatments. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 235-238
- Lehringer, C.; Arnold, M.; Richter, K.; Schubert, M.; Schwarze, F. W. M. R.; Militz, H.: Bioincised Wood as Substrate for Surface Modifications. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 197-200
- Mai, C.; Verma, P. Xie, Y.; Dyckmans, J.; Militz, H.: Mode of Action of DMDHEU Treatment against Wood Decay by White and Brown Rot Fungi. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 45-52

- Militz, H.; Lande, S.: Challenges in Wood Modification Technology on the way to Practical Applications. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 3-11
- Puttmann, S.; Krause, A.; Pilgård, A.; Treu, A.; Militz, H.: Furfurylated Wood for Wooden Window Constructions. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 569-576
- Scholz, G.; Krause, A.; Militz, H.: Capillary Water Uptake and Mechanical Properties of Wax Soaked Scots Pine. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 209-212
- Trinh, H. M.; Militz, H.; Mai, C.: Performance Testing of Plywood from Beech Veneers Treated with Melamine-based Compounds. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 429-438
- Verma P, Junga U, Militz H, Mai C (2009) Protection mechanisms of DMDHEU treated wood against white and brown rot fungi. HOLZFORSCHUNG, 63: 371-378
- Wolkenhauer A, Avramidis G, Hauswald E, Loose S, Viöl W, Militz H (2009) Investigations on the drying behaviour on plasma-treated wood materials. WOOD RES-SLOVAKIA, 54 (1): 59-66
- Xiao, Z.; Xie, Y.; Militz, H., Mai, C.: Modification of Wood with Glutaraldehyde. In: Englund, F.; Hill, C. A. S.; Militz, H.; Segerholm, B. K. (Hg.). Proceedings of the 4th European Conference on Wood Modification, 27-29 April 2009, Stockholm, Sweden, 411-418

2008

- Dieste, A.; Krause, A., Militz, H. (2008): Modification of *Fagus sylvatica* (L.) with 1,3-dimethylol-4,5-dihydroxyethylene urea (DMDHEU): Part 1. Estimation of heat adsorption by the isotheric method (Hailwood-Horrobin model) and by solution calorimetry. *Holzforschung* 62: 577-583
- Dieste, A.; Krause, A.; Bollmus, S.; Militz H. (2008): Physical and mechanical properties of plywood produced with 1.3-dimethylol-4.5-dihydroxyethyleneurea (DMDHEU)-modified veneers of *Betula* sp. and *Fagus sylvatica*. *Holz als Roh- und Werkstoff* 66: 281-287
- Dieste, A.; Mai, C.; Militz, H., Oliver, J. V. (2008): Nuevas alternativas a los métodos de preservación de la madera. *Comercio e Industria de la Madera* 161, Septiembre/Octubre: 55-59
- Dieste, A.; Pfeffer, A.; Bollmus, S.; Militz, H. (2008): Resistance against basidiomycetes of 1.3-dimethylol-4.5-dihydroxy ethylene urea (DMDHEU)-modified plywood of *Pinus*

- sylvestris*. International Research Group on Wood Protection. Document 08-40398, 39th Annual Meeting, Istanbul, Türkei
- Gelbrich, J.; Mai, C.; Militz, H. (2008): Chemical changes in wood degraded by bacteria. Int. Biodeterioration & Biodegradation 61: 24-32
- Ghosh, S.C.; Mai, C.; Militz, H. (2008): The efficacy of commercial silicones against blue stain and mould fungi in wood. International Research Group on Wood Protection. Document 08-30471, 39th Annual Meeting, Istanbul, Türkei
- Hapla, F., Militz, H. (2008): Verwertung und Verwendung von Buchenholz (Utilisation of beech wood). Beiträge aus der NW-FVA, Band 3: 311-325
- Krause, A.; Wepner, F.; Xie, Y.; Militz, H. 2008: Wood protection with Dimethyloldihydroxy-Ethyleneurea and its derivatives. In: Schultz, T. P.; Militz, H.; Freeman, M. H.; Goodell, B.; Nicholas, D. D.: Development of Commercial Wood Preservatives. Efficacy, Environmental, and Health Issues. Oxford University Press: 356-371
- Kretschmar, E. I.; Gelbrich, J.; Militz, H.; Lamersdorf, N. (2008): Studying bacterial wood decay under low oxygen conditions – results of microcosm experiments. Int. Biodeterioration & Biodegradation 61: 69-84
- Kurt R, Kraus A, Militz H, Mai C (2008) Hydroxymethylated resorcinol (HMR) priming agent for improved bondability of wax-treated wood. HOLZ ROH WERKST, 66: 333-338.
- Kurt R, Krause A, Militz H, Mai C (2008) Hydroxymethylated resorcinol (HMR) priming agent for improved bondability of silicone modified wood glued with a polyvinyl acetate adhesive. HOLZ ROH WERKST, 66: 305-307.
- Militz, H. (2008): Processes and properties of thermally modified wood manufactured in Europe. In: Schultz, T. P.; Militz, H.; Freeman, M. H.; Goodell, B.; Nicholas, D. D.: Development of Commercial Wood Preservatives. Efficacy, Environmental and Health Issues. Oxford University Press: 372-388
- Militz, H.; Rademacher, P. (2008): Buchenholz für den Außeneinsatz. Technologie-Informationen 4: 5
- Militz, H.; Schaffert, S.; Peters, B.C.; Fitzgerald, C.J. (2008): Termite resistance of DMDHEU-treated wood. International Research Group on Wood Protection. Document 08-40401, 39th Annual Meeting, Istanbul, Türkei
- Militz, H.; Scholz, G. (2008): Holzmodifizierung statt Tropenholz. Technologie-Informationen 4: 5
- Nicholas, D. D.; Militz, H. (2008): Concepts in the development of new accelerated test methods for wood decay. In: Schulz, T. P.; Militz, H.; Freeman, M. H.; Goodell, B.; Nicholas, D. D. (Hg.): Development of Commercial Wood Preservatives. Efficacy, Environmental and Health Issues. Oxford University Press: 142-151

- Schultz, T. P.; Militz, H.; Freeman, M. H.; Goodell, B., Nicholas, D. D. (2008): Development of Commercial Wood Preservatives. Efficacy, Environmental and Health Issues. ACS Symposium Series 982, ISBN 978-0-8412-3951-7
- Schultz, T. P.; Militz, H.; Freeman, M. H.; Goodell, B.; Nicholas, D. D. (2008 Eds.): Development of Commercial Wood Preservatives. Efficacy, Environmental, and Health Issues. ACS Symposium Series 982. Oxford University Press. ISBN 978-0-8412-3951-7
- Treu, A.; Rieche, H.; Militz, H. (2008): Spruce and pine heartwood treatment by means of microwave radiation. International Research Group on Wood Protection. Document 08-40411, 39th Annual Meeting, Istanbul, Türkei
- Verma, P., Dyckmans, J., Militz, H., Mai, C. (2008) Determination of fungal activity in modified wood by means of micro-calorimetry and determination of total esterase activity. Appl. Microbiol. Biotechnol. 80:125-133
- Weigenand, O.; Humar, M.; Daniel, G.; Militz, H.; Mai, C. (2008): Decay resistance of wood treated with amino-silicone compounds. *Holzforschung* 62: 112-118
- Wolkenhauer, A.; Avramidis, G.; Hauswald, E., Militz, H.; Viöl, W. (2008): Plasmabehandlung von Holz-Kunststoff-Kompositen und Spanplatten. *Holztechnologie* 49: 4, 22-27
- Wolkenhauer, A.; Avramidis, G.; Militz, H.; Viöl, W. (2008): Plasma treatment of heat treated beech wood – investigation on surface free energy. *Holzforschung* 62: 472-474
- Wolkenhauer, A.; Militz, H.; Viöl, W. (2008): Increased PVA-Glue adhesion on particle board and fibre board by plasma treatment. *Holz als Roh- und Werkstoff* 66: 143-145
- Xie, Y.; Krause, A.; Militz, H.; Mai, C. (2008): Weathering of uncoated and coated wood treated with methylated 1,3-dimethylol-4,5-dihydroxyethyleneurea(mDMDHEU). *Holz als Roh- und Werkstoff* 66: 455-464

2007

- Danzig, J.; Jelen, E.; Deerberg, G.; Kareth, S.; Weidner, E.; Mai, C.; Ghosh, S.C.; Militz, H. (2007): Modifizierung einheimischer Hölzer durch Imprägnierung mit überkritischem Kohlendioxid als Lösungsmittel. Schriftenreihe „Nachwachsende Rohstoffe“ Band 30. Nachwachsende Rohstoffe für die Chemie, 10. Symposium 2007. 259-260 ISBN: 978-3-9803927-0-9
- Dieste, A.; Krause, A.; Bollmus, S.; Militz, H. (2007): Performance testing of plywood produced with DMDHEU-modified veneers of *Fagus sp.*, *Betula sp.*, and *Picea sp.*. Int. Panel Products Symposium 2007, 16-19 Oct. UK
- Donath, S.; Militz, H.; Mai, C. (2007): Weathering of silane treated wood. *Holz als Roh- und Werkstoff* 65: 35-42
- Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd, G. A. (2007): European Conference on Wood Modification. The 3rd European Conference on Wood Modification. Bangor, UK, 15-16 Oct. 2007. ISBN: 184-220-096-8

- Jelen, E.; Danzig, J.; Deerberg, G.; Kareth, S.; Weidner, E.; Mai, C.; Ghosh, S.; Militz, H. (2007): Modifizierung einheimischer Hölzer durch Imprägnierung mit überkritischem Kohlendioxid als Lösungsmittel. Vortrag. FA Sitzungen „Mehrphasenströmungen“ und „Hochdruckverfahrenstechnik“, Baden-Baden, 7-8 März 2007
- Jelen, E.; Danzig, J.; Deerberg, G.; Kareth, S.; Weidner, E.; Mai, C.; Ghosh, S.; Militz, H. (2007): Modification of domestic timbers by impregnation using supercritical carbon dioxide – Preliminary results. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). The Third European Conference on Wood Modification. Bangor, 2007, UK, 291-294
- Kües, U.; Mai, C.; Militz, H. (2007): Biological Wood Protection against Decay, Microbial Staining, Fungal Moulding and Insect Pests. In: Wood production, wood technology, and Biotechnological Impacts (U. Kües, ed.). Universitätsverlag Göttingen. ISBN 978-3-940344-11-3. S.273-294
- Kurt, R.; Mai, C.; Krause, A.; Militz, H. (2007): Hydroxymethylated resorcinol (HMR) priming agent for improved bondability of silicone modified wood. Bonding of Modified Wood Proceedings of the 5th COST E34 International Workshop. Ljubljana, Slovenia, 2007: 71-76
- Mai, C.; Militz, H. (2007): Wood Preservatives and Wood Protection. In: Wood production, wood technology, and Biotechnological Impacts (U. Kües, ed.). Universitätsverlag Göttingen. ISBN 978-3-940344-11-3. S.259-271
- Mai, C.; Weigenand, O.; Ghosh, S.; Militz, H. (2007): Effects of wood treatment with amino-silicone emulsions on different material properties. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). The Third European Conference on Wood Modification. Bangor, 2007, UK, 105-114
- Mai, C.; Nguyen, M. H.; Donath, S.; Weigenand, O.; Militz, H. (2007): Neuartige Systeme zur Hydrophobierung von Holz in der Außenanwendung. Wege zum geschützten Holz im modernen Holzbau. Biberach, S. 73-85
- Mai, C.; Xie, Y.; Xiao, Z.; Bollmus, S.; Vetter, G.; Krause, A.; Militz, H. (2007): Influence of the modification with different aldehyde-based agents on the tensile strength of wood. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). The Third European Conference on Wood Modification, Bangor, UK, 49-56
- Minh, H. N.; Militz, H.; Mai, C. (2007): Weathering properties of wood modified with hydrophobation agents. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). The Third European Conference on Wood Modification, Bangor, 2007, UK, 205-208
- Nguyen, H. M.; Militz, H.; Mai, C. (2007): Protection of wood for above ground application through modification with a fatty acid modified N-methylol/paraffin formulation. International Research Group on Wood Preservation. Document 07-40378, 38th Annual Meeting, Jackson Lake Lodge, Wyoming, USA, 2007
- Nguyen, M.H.; Militz, H., Mai, C. (2007): Weathering Properties of Wood Modified with Hydrophobation Agents. In: Hill CAS, Jones D, Militz H, Ormondroyd GA (Hg.) The

Third European Conference on Wood Modification. The Third European Conference on Wood Modification, Bangor, UK, 205-208.

- Petrič, Marco; Knehtl, Brane; Krause, Andreas; Militz, Holger; Pavlič; Matjaž; Pétrissans, Mathieu; Rapp, Andreas; Tomažič, Miro; Welzbacher, Christian; Gérardin, Philippe (2007): Wettability of waterborne coatings on chemically and thermally modified pine wood. *Journ. of Coatings Technology and Research*, 4 (2) 203-206
- Schirp, A.; Stoll, B.; Mai, C.; Richter, E.; Militz, H. (2007): Chemical modification of wood particles for the production of WPCs using N-Methylol compounds and paraffin. 9th International Conference on Wood & Biofiber plastic composites, Madison, Wisconsin, USA, 21-23 Mai 2007. S. 243-252 ISBN 1-892529-50-5
- Tingaut, P.; Weigenand, O.; Mai, C.; Militz, H.; Sébe, G. (2007): Fixation of methyltrimethoxysilane in wood pre-modified with an alkoxy silane coupling agent. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). *The Third European Conference on Wood Modification*. Bangor, 2007, UK, 143-146
- Treu; A.; Larnøy, E.; Militz, H. (2007): Microwave curing of furfuryl alcohol modified wood. International Research Group on Wood Preservation. Document 07-40371, 38th Annual Meeting, Jackson Lake Lodge, Wyoming, USA, 2007
- Weigenand, O.; Militz, H.; Tingaut, P.; Sèbe, G.; de Jeso, B.; Mai, C. (2007): Penetration of amino-silicone micro- and macro-emulsions into Scots pine sapwood and the effect on water-related properties. *Holzforschung* 61: 51-59
- Wolkenhauer, A.; Avramidis, G.; Militz, H.; Viöl, W. (2007): Wood modification by atmospheric pressure plasma treatment. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). *The Third European Conference on Wood Modification*. The 2007, UK, 271-274
- Wolkenhauer, A.; Avramidis, G.; Hauswald, E.; Militz, H.; Viöl, W. (2007): Sanding vs. plasma treatment of aged wood: A comparison with respect to surface energy. *Intern. Journal of Adhesion & Adhesives*. DOI: 10.1016/j.ijadhadh.2007.11.001 [1,250]
- Wolkenhauer, A.; Avramidis, G.; Cai, Y.; Militz, H.; Viöl, W. (2007): Investigation of wood and timber surface modification by dielectric barrier discharge at atmospheric pressure. *Plasma Processes and Polymers* 4: 470-474 [2,298] ISSN 1612-8869
- Xie, Y.; Krause, A.; Militz, H.; Mai, C. (2007): Weathering and coating properties of chemical modified wood. In: Hill, C. A. S.; Jones, D.; Militz, H.; Ormondroyd G. A. (Hg.). *The Third European Conference on Wood Modification*. Bangor, 2007, UK, 213-216
- Xie, Y.; Krause, A.; Militz, H.; Turkulin, H.; Richter, K.; Mai, C. (2007): Effect of treatments with 1,3-dimethylol-4,5-dihydroxy-ethyleneurea (DMDHEU) on the tensile properties of wood. *Holzforschung* 61: 43-50

2006

- Alfredsen, G.; Larnøy, E.; Militz, H. (2006): Dynamic moe testing of wood: The influence of wood protecting agents and moisture content on ultrasonic pulse and resonant vibration. *Wood research* 51 (1): 11-20
- Bartholme, M.; Wepner, F.; Krause, A.; Militz, H.; Kharazipour, A. (2006): Novel particleboards made of cross-linked chips. 6th Global Wood and Natural Fibre Composites Symposium. Kassel 05-06 April 2006, B5-1 bis B5-12
- Boonstra, M.J.; Rijdsdijk, J.F.; Sander, C.; Kegel, E.; Tjeersdsma, B.; Militz, H.; van Acker, J.; Stevens, M. (2006): Microstructural and physical aspects of heat treated wood. Part 1. *Softwoods. Maderas, Ciencia y Tecnologia* 8 3: 193-208. ISSN 0718-221X
- Boonstra, M.J.; Rijdsdijk, J.F.; Sander, C.; Kegel, E.; Tjeersdsma, B.; Militz, H.; van Acker, J.; Stevens, M. (2006): Microstructural and physical aspects of heat treated wood. Part 2. *Hardwoods. Maderas, Ciencia y Tecnologia* 8 3: 209-218. ISSN 0718-221X
- Donath, S.; Militz, H.; Mai, C. (2006): Creating water-repellent effects on wood by treatment with silanes. *Holzforschung* 60: 40-46
- Donath, S.; Militz, H.; Mai, C. (2006): Treatment of wood with aminofunctional silanes for protection against wood destroying fungi. *Holzforschung* 60: 210-216
- Joščák, T.; Krause, A.; Treu, A.; Militz, H. (2006): Determination of moisture content of resin modified wood. *Wood Research* 51 (4): 37-46
- Larnøy, E.; Alfredsen, G.; Militz, H. (2006): Moisture correction for ultrasonic MOE measurements above fibre saturation point in Scots pine sapwood. International Research Group on Wood Preservation. Document 06-20333, 37th Annual Meeting, Tromsø, Norway
- Larnøy, E.; Dantz, S.; Eikenes, M.; Militz, H. (2006): Screening of properties of modified chitosan-treated wood. *Wood Material Science and Engineering* 1: 59-68
- Militz, H. (2006): Aspekte des Holzschutzes bei der Industrie und im Wohnungsbau – Neuartige Verfahren der Holzmodifizierung. 12. Quedlinburger Holzbautagung „Holz am Bau – Schutz für die Zukunft“, 30.-31. März 2006
- Militz, H.; Krause, A.: Vergütung von Laubholz. Laubholzkongress 2006, Hohenheim
- Rademacher, P.; Militz, H.; Albrecht, C. M.; Bollmus, S.; Hansen, J, Krause, A.; Schwerdtfeger, L.; Welling, H. (2006): 1. Zwischenbericht im BMBF-Vorhaben Nachhaltige Waldwirtschaft. Georg-August-Universität Göttingen
- Schaffert, S.; Nunes, L.; Krause, A.; Militz, H. (2006): Resistance of DMDHEU-treated pine wood against termite and fungi attack in field testing according to EN 252. Results after 30 months. International Research Group on Wood Preservation. Document 06-40354, 37th Annual Meeting, Tromsø, Norway, 18-22 June 2006

- Tingaut, P.; Weigenand, O.; Mai, C.; Militz, H.; Sèbe, G. (2006): Chemical reaction of alkoxy-silane molecules in wood modified with silanol groups. *Holzforschung* 60: 271-277
- Wepner, F.; Bartholme, M.; Militz, H. (2006): Formstabile und dauerhafte Holzwerkstoffe durch Holzmodifizierung. 3. Fachtagung „Umweltschutz in der Holzwerkstoffindustrie“. 18. und 19. Mai 2006 in Göttingen. Tagungsband: 27-33
- Wepner, F.; Krause, A.; Militz, H. (2006): Weathering resistance of N-methylol-treated plywood panels. Proceedings of the Second International Symposium of veneer processing and products. Fachtagung. Vancouver BC, Canada: 305-314
- Xie, Y.; Krause, A.; Militz, H.; Mai, C. (2006): Effect on coating performance of chemical modification of wood substrates with cyclic *N*-Methylol compound. European Coatings Conference. "Parquet Coatings IV". Berlin, Germany, Nov., 9th-10th 2006: 1-8
- Xie, Y.; Krause, A.; Militz, H.; Mai, C. (2006): Coating performance of finishes on wood modified with an *N*-methylol compound. *Progress in Organic Coatings* 57: 291-300

2005

- Chirkova, J.; Andersons, B.; Andersone, I.; Militz, H. (2005): Water sorption properties of thermo-modified wood. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The second European Conference on Wood Modification ECWM, Göttingen: 65-69
- Donath, S.; Mai, C.; Militz, H. (2005): Untersuchungen zur Eignung von Silanen als Holzbehandlungsmittel. *Schweizerische Zeitschrift für Forstwesen* 156, 11: 411-413
- Eikenes, M.; Alfredsen, G.; Larnøy, E.; Militz, H.; Kreber, B.; Chittenden, C. (2005): Chitosan for wood protection – state of the art. International Research Group on Wood Preservation. Document 05-30378, 36th Annual Meeting, Bangalore, India, 24-28 April 2005, 1-1
- Eikenes, M.; Alfredsen, G.; Larnøy, E.; Militz, H.; Kreber, B.; Chittenden, C. (2005): Chitosan for wood protection – state of the art and opportunities. 36th Annual Meeting COST Action E37 – Workshop. Managing the Environmental Risk, Bangalore, India
- Junga, U.; Militz, H. (2005): Particularities in Agar Block Tests of some modified woods caused by different protection and decay principles. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 354-362
- Junga, U.; Militz, H. (2005): Besonderheiten bei der biologischen Prüfung einiger modifizierter Hölzer. Probleme durch unterschiedliche Schutz- und Abbauprinzipien. Sicherung von Produktqualität und –leistung. 24. Holzschutztagung der DGfH, Leipzig 12.-13. April 2005: 139-147
- Krause, A.; Militz, H.: Properties of modified wood coated with different stains. In: Militz, H.; Hill, C. (Hg (2005)): Wood modification: Processes, properties and

- commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 289-294
- Larnøy, E.; Eikenes, M.; Militz, H. (2005): Solution stability and mechanical properties of Chitosan treated pine. International Research Group on Wood Preservation. Document 05-30377, 36th Annual Meeting, Bangalore, India, 24-28 April 2005 1-1
- Larnøy, E.; Eikenes, M.; Militz, H. (2005): Uptake of chitosan based impregnation solutions with varying viscosities in four different european wood species. Holz als Roh- und Werkstoff 63: 456-462
- Larnøy, E.; Dantz, S.; Eikenes, M.; Militz, H. (2005): Screening of properties of modified chitosan-treated wood. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 263-269
- Mai, C.; Donath, S.; Weigenand, O.; Militz, H. (2005): Aspects of wood modification with silicon compounds: Material properties and process development. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 222-231
- Militz, H.; Mai, C. (2005): Im (Holz-) Kern verändert. Georgia Augusta, 4: 128-135
- Militz, H.; Meyer, U. (2005): Entwicklung neuer Verfahren für den Fensterbau. Jahrestagung der Akzo Nobel Coatings, Hülse
- Militz, H.; Meyer, U.; Krause, A. (2005): Geeignete Beschichtungssysteme für dimensionsstabilisierte Hölzer. Holz Innovativ, Rosenheim
- Militz, H.; Larnøy, E.; Eikenes, M.; Alfredsen, G. (2005): Chitosan als Holzschutzmittel. Ein Naturstoff aus Bioabfällen. Sicherung von Produktqualität und –leistung. 24. Holzschutztagung der DGfH. 12-13 April 2005 Leipzig. S. 149-156
- Minh, N.; Mai, C.; Hung, N.; Khanh, N.; Militz, H. (2005): Durability properties of rubber and paulownia wood treated by hydrophobation agents. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 309-313
- Schaffert, S.; Krause, A.; Militz, H. (2005): Upscaling and process development for wood modification with *N*-methylol Compounds using superheated steam. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM. Göttingen: 161-168
- Schwarz, B.; Schmid, J.; Krause, A.; Militz, H. (2005): Fenster und Fassaden aus modifizierten Hölzern – Projektergebnisse und weitere Schritte zur Umsetzung. Sicherung von Produktqualität und –leistung. 24. Holzschutztagung der DGfH am 12. und 13. April 2005 in Leipzig. S. 179-189
- Tingaut, P.; Weigenand, O.; Militz, H.; de Jéso, B.; Sèbe, G. (2005): Functionalisation of wood by reaction with 3-isocyanatopropyltriethoxysilane: Grafting and hydrolysis of the triethoxysilane end groups. Holzforschung 59: 397-404

Tingaut, P.; Weigenand, O.; Militz, H.; de Jéso, B.; Sèbe, G. (2005): Chemical grafting of reactive Triethoxysilane end groups in maritime pine sapwood (*Pinus pinaster* Soland). In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 215-221

Tjeerdsma, B. F.; Militz, H. (2005): Chemical changes in hydrothermal treated wood: FTIR analysis of combined hydrothermal and dry heat-treated wood. Holz als Roh- und Werkstoff 63: 102-111

Verma, P.; Mai, C.; Krause, A.; Militz, H. (2005): Studies on the resistance of DMDHEU treated wood against white-rot and brown-rot fungi. International Research Group on Wood Preservation. Document 05-10566, 36th Annual Meeting, Bangalore, India, 24-28 April 2005: 1-1

Weigenand, O.; Mai, C.; Babiak, M.; Militz, H. (2005): Comparative Investigation on some physical properties of modified wood. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM. Göttingen: 295-297

Wepner, F.; Militz, H. (2005): Fungal resistance, dimensional stability and accelerated weathering performance of *N*-Methylol treated veneers of *Fagus sylvatica*. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference of Wood Modification ECWM, Göttingen: 169-177

Xie, Y.; Krause, A.; Mai, C.; Militz, H.; Richter, K.; Urban, K.; Evans, P. D.: Weathering of wood modified with the *N*-methylol compound 1,3-dimethylol-4,5-dihydroxyethyleneurea. Polymer Degradation and Stability 89 (2005): 189-199

Xie, Y.; Krause, A.; Mai, C.; Militz, H.; Richter, K.; Urban, K.; Evans P. D. (2005): Artificial Weathering of wood modified with the cyclic *N*-Methylol compounds. In: Militz, H.; Hill, C. (Hg): Wood modification: Processes, properties and commercialisation. The Second European Conference on Wood Modification ECWM, Göttingen: 363-366

2004

Alfredsen, G.; Eikenes, M.; Militz, H.; Solheim, H. (2004): Screening of chitosan against wood-deteriorating fungi. Scand. J. For. Res. 19, Suppl. 5: 4-13

Alfredsen, G.; Flæte, P. O.; Temiz, A.; Eikenes, M.; Militz, H. (2004): Screening of the efficacy of tall oils against wood decaying fungi. International Research Group on Wood Preservation. Document 04-30354, 35th Annual Meeting Ljubljana, Slovenia

Donath, S.; Militz, H.; Mai, C. (2004): Wood modification with alkoxy-silanes. Wood Science and Technology 38: 555-566

Hapla, F.; Militz, H. (2004): Colour measurements and gluability investigation on red heart beech wood (*Fagus sylvatica* L.). Wood Research 49, 4: 1-12

Krause, A.; Militz, H. (2004): Cyclic *N*-Methylol compounds for wood modification. . Proceedings of the International Symposium on Advanced Timber and Timber-

Composite Elements for Buildings. COST E29 – Florence – 27-29 October 2004: 131-139

Krause, A.; Hof, C.; Militz, H. (2004): Novel wood modification processes for window and cladding products. International Research Group on Wood Preservation. Document 04-40285, 35th Annual Meeting Ljubljana, Slovenia

Kürsten, E.; Militz, H. (2004): Possibilities for the use of the different types of wood residues as raw material. Proceedings of the International Symposium, Thessaloniki: 190-203

Machek, L.; Militz, H. (2004): The influence of the location of a wood defect on the modulus of elasticity determination in wood durability testing. International Research Group on Wood Preservation. Document 04-20287, 35th Annual Meeting Ljubljana, Slovenia

Mai, C.; Militz, H. (2004): Modification of wood with silicon compounds. Inorganic silicon compounds and sol-gel systems: a review. Wood Science and Technology 37: 339-348

Mai, C.; Militz, H. (2004): Modification of wood with silicon compounds. Treatment systems based on organic silicon compounds – a review. Wood Science and Technology 37: 453-461

Mai, C.; Kües, U.; Militz, H. (2004): Biotechnology in the wood industry. Applied Microbiology Biotechnol. 63: 477-494

Militz, H.; Krause, A. (2004): Tuning für Buche & Co. Fenster-Magazin, Supplement von Holz-Zentralblatt und HK: 46-49

Militz, H.; Krause, A.; Hof, C. (2004): Modified wood for window and cladding products. Proceedings of the International Symposium on Advanced Timber and Timber-Composite Elements for Buildings. COST E29 – Florence – 27-29 October 2004: 141-150

Schulte, Y.; Donath, S.; Krause, A.; Militz, H. (2004): Evaluation of outdoor weathering performance of modified wood. International Research Group on Wood Preservation. Document 04-20296, 35th Annual Meeting Ljubljana, Slovenia

Treu, A.; Lückers, J.; Militz, H. (2004): Screening of modified linseed oils on their applicability in wood protection. International Research Group on Wood Preservation. Document 04-30346, 35th Annual Meeting Ljubljana, Slovenia

2003

Hapla, F.; Militz, H. (2003): Colour measurements and gluability investigation on red heart beech wood (*Fagus sylvatica* L.). Proceedings of Intern. Conference “Issues of heartwood research and utilisation in Europe”, September 2003, Sopron

Illner, M.; Militz, H.; Schmid, J.; Schwarz, B.; Stetter, K. (2003): Modifizierte Hölzer für den Einsatz im Fensterbau. Holzzentralblatt 129 (47): 698

- Krause, A.; Jones, D.; van der Zee, M.; Militz, H. (2003): Interlace treatment- wood modification with N-methylol compounds. European Conference on Wood Modification, Ghent: 317-327
- Machek, L.; Edlund, M.L.; Sierra-Alvarez, R.; Militz, H. (2003): A non-destructive approach approach for assessing decay in preservative treated wood. Wood Science and Technology 37: 411-417
- Mai, C.; Donath, S.; Militz, H. (2003): Modification of wood with silicon compounds. European Conference on Wood Modification, Ghent: 239-251
- Mai, C.; Donath, S.; Militz, H. (2003): Einsatz von Siliziumverbindungen zur Holzvergütung. 23. Holzschutztagung der DGFH, Augsburg: 83-96
- Militz, H., Krause, A. (2003): Neuartige Verfahren der Holzmodifizierung für den Fenster- und Fassadenbau. Rosenheimer Fenstertage: 101-106
- Militz, H.; Busetto, D.; Hapla, F. (2003): Investigation on natural durability and sorption properties of Italian Chestnut (*Castanea sativa* Mill.) from coppice stands. Holz als Roh- und Werkstoff 61: 133-141
- Militz, H.; Son, D.W.; Gomez-Hernandez, L.; Sierra-Alvarez, R. (2003): Effect of fungal degradation on the chemical composition of acetylated beech wood. International Research Group on Wood Preservation, Document 03-40267, 34th Annual Meeting Brisbane, Australia
- Mohebbi, B.; Mai, C.; Militz, H. (2003): Soft rot decay in acetylated wood: microcalometry and ergosterol assay in decayed wood. Proceedings of the International Symposium, European Conference on Wood Modification, Ghent: 197 – 202
- Sander, C.; Beckers, E.P.J.; Militz, H.; van Veenendaal, W. (2003): Analysis of acetylated wood by electron microscopy. Wood Science and Technology 37: 39-46
- Tomazic, M.; Kricej, B.; Pavlic, M.; Petric, M.; Mai, C.; Militz, H. (2003): Properties of silane treated and coated wood. Proceedings of 5th Int. Conf. on Wood Techn., Constr. Industry and Wood Protection, Zagreb: 27-33
- Treu, A.; Militz, H.; Breyne, S. (2003): Royal-treatment – scientific background and practical application. Proceedings of the International Symposium: 7-15
- Treu, A.; Habicht, J.; Klauke, R.; Militz, H. (2003): Improvement of wood properties by a combined impregnation process- the Royal process. European Conference on Wood Modification, Ghent: 3-13
- Treu, A.; Militz, H.; Habicht, R.; Klauke, R. (2003): Kombinationsverfahren von bioziden Holzschutzmitteln und Hydrophobierungsmitteln. 23. Holzschutztagung der DGFH, Augsburg: 177-193
- van Acker, J.; Stevens, M.; Carey, J.; Sierra-Alvarez, R.; Militz, H.; Le-Bayon, I.; Kleist, G.; Peek, R.D. (2003): Biological durability of wood in relation to end-use - Part 1. Towards a European standard for laboratory testing of the biological durability of wood. Holz als Roh- und Werkstoff 61: 35-45

van Eckevelde, A.; Homan, W. J.; Militz, H. (2003): Water repellency of some natural oils. Oils and water repellents in wood preservation. Proceedings of the International Symposium, Reinbeck: 41-46

2002

Hapla, F.; Meggers, L.; Militz, H.; Mai, C. (2002): Investigation on the yield and quality of sliced veneers produced from beech trees (*Fagus sylvatica* L.) containing red heartwood. Holz als Roh- und Werkstoff 60: 440-442

Militz, H. (2002): Heat treatment technologies in Europe: Scientific background and technological state-of-art. Proceedings of FPRS Conference „Enhancing durability of lumber and engineered wood products“, Florida, USA: 239-249

Militz, H. (2002): Thermal treatment of wood: European processes and their background. International Research Group on Wood Preservation, Document 02-40241, 33rd Annual Meeting Cardiff, UK

Militz, H. (2002): Solid wood modification. Proceedings Part 1, Cost E13 Int. Symposium on Wood Based Materials: Wood Composites and Chemistry. 19.-20.9.2002 Vienna, Austria, 1

Militz, H. (2002): Modified wood. A new material for new and existing markets. Proceedings of 1st European Wood Conference “Wood industry in Europe-growing together”. Hamburg 10.10.2002: 69-74

Mohebbi, B.; Militz, H. (2002): Soft rot decay in acetylated wood. Chemical and anatomical changes in decayed wood. International Research Group on Wood Preservation, Document 02-40231, 33rd Annual Meeting Cardiff, UK

Stuber, B.; Militz, H.; Weihs, U.; Krummheuer, F. (2002): Nomenklatur und Physiologie der fakultativen Kernbildung von Rotbuche (*Fagus sylvatica* L.). Forst und Holz 57: 129-133

Tjeerdsma, B.F., Stevens, M., Militz, H., van Acker, J. (2002): Effect of process conditions on moisture content and decay resistance of hydro-thermally treated wood. Holzforschung und -verwertung 54, 5: 94-99

2001

de Meijer, M.; Militz, H. (2001): Moisture transport in coated wood. Part 2: Influence of coating type, film thickness, wood species, temperature and moisture gradient on kinetics of sorption and dimensional change. Holz als Roh- und Werkstoff 58: 467-475

de Meijer, M.; Thurich, K.; Militz, H. (2001): Quantitative measurements of capillary coating penetration in relation to wood and coating properties. Holz als Roh- und Werkstoff 59: 35-45

- de Meijer, M.; Velde, B. van de; Militz, M. (2001): Rheological approach to the capillary penetration of coating into wood. *Journal of Coatings Technology* 73, 914: 39-51
- Hapla, F.; Militz, H. (2001): On the importance of wood quality against the background of ecological silviculture. - Contemplation of relevant silvicultural mixed-stand systems. Proceedings of the 5th Workshop COST-Action E10 "Wood Properties for Industrial Uses", Hurdal, Norway
- Machek, L.; Militz, H.; Sierra-Alvarez, R. (2001): The influence of wood moisture content on dynamic modulus of elasticity measurements in durability testing. *Holzforschung und -verwertung* 53, 5: 97-100
- Machek, L.; Militz, H.; Sierra-Alvarez, R. (2001): The use of an acoustic technique to assess wood decay in laboratory soil-bed tests. *Wood Science and Technology* 34: 467-472
- Militz, H. (2001): Oils and water repellents in wood preservation. Proceedings of a special seminar of COST E22, Reinbek 2001, 65 Seiten (Editor)
- Rijckaert, V.; Stevens, M.; van Acker, J.; de Meijer, M.; Militz, H. (2001): Quantitative assessment of the penetration of water-borne and solvent-borne wood coatings in Scots pine sapwood. *Holz als Roh- und Werkstoff* 59: 278-287
- Treu, A.; Militz, H.; Breyne, S. (2001): Royal-treatment - scientific background and practical application. European Conference of COST E22, Reinbek, Germany
- van Ekeveld, A.; Homan, W.J.; Militz, H. (2001): Water repellency of some natural oils. European Conference of COST E 22, Reinbek, Germany
- van Ekeveld, A.; Homan, W.J.; Militz, H. (2001): Increasing the water repellency of Scots pine sapwood. *Holzforschung und -verwertung* 53, 6: 113-115

2000

- de Meijer, M.; Militz, H. (2000): Adhesion of low-VOC-coatings on wood: a quantitative analysis. *Progress in Organic Coatings* 28: 223-240

- de Meijer, M.; Militz, H. (2000): Moisture transport in coated wood. Part 1: Analysis of sorption rates and moisture content profiles in spruce during liquid water uptake. *Holz als Roh- und Werkstoff* 58: 354-362
- Militz, H.; Tjeerdsma, B. (2000): Heat treatment of wood by the "PLATO-Process". Proceedings of heat treatment conferences, Helsinki, Stockholm, Oslo
- Militz, H.; van Acker, J. (2000): Wood modification towards practical application. A european perspective. IUFRO World Conference, Kuala Lumpur, Malaysia
- Militz, H. (2000): Alternative Schutz- und Behandlungsverfahren. 22. Deutsche Holzschutz-Tagung, Bad Kissingen
- Militz, H.; Bloom, C.J. (2000): The use of lap-joints in natural durability testing: Moisture content development during 36 months outside exposure trials. International Research Group on Wood Preservation, Document WP 00-20217, Hawaii, USA
- Sundell, P.; de Meijer, M.; Militz, H. (2000): Preventing light induced degradation of wood by acetylation: A study on lignin and lignin model compounds. In: Second Wood Coatings Conference "Wood Coatings, Challenges and Solutions in the 21th Century, The Hague, The Netherlands
- Tjeerdsma, B.F.; Stevens, M.; Militz, H. (2000): Durability aspects of (hydro)thermal treated wood. International Research Group on Wood Preservation, Document WP 00-40160, Hawaii, USA

1999

- Acker, J. van, Militz, H., Stevens, M. (1999): The significance of accelerated laboratory testing methods for determining the natural durability of wood. *Holzforschung*: 449-458.
- Meijer, M. de, Militz, H. (1999): Sorption behaviour and dimensional changes of wood coatings composites. *Holzforschung*: 553-560.
- Meijer, M. de, Militz, M. (1999): Adhesion of low-VOC coatings on wood: a quantitative analysis. *Verfkroniek* 4: 25-30.
- Polman, J.E., Michon, S.G.L., Militz, H., Helmink, A.T.F. (1999): The wood of *Metasequoia glyptostroboides* (Hu en Cheng) of Dutch origin. *Holz als Roh und Werkstoff*: 215-221

1998

- Acker, J. van, Stevens, M., Carey, J., Sierra-Alvarez, R., Militz, H., Le Bayon, I., Kleist, G., Peek, R-D. (1998): Criteria for basidiomycete testing and ways of defining natural durability classes. The International Research Group on Wood Preservation, Document WP 98-20144, Maastricht, The Netherlands.
- Beckers, E.P.J., De Meijer, M., Militz, H., Stevens, M. (1998): Performance of finishes on wood that is chemically modified by acetylation. *Journal of Coatings Technology*. Vol. 70. No 878: 59-67.

Meijer, M. de, Thurich, K., Militz, H. (1998): Comparative study on penetration characteristics of modern wood coatings. *Wood Science and Technology*: 347-365.

Meijer, M. de, Militz, H. (1998): Wet adhesion measurements of wood coatings. *Holz als Roh- und Werkstoff* 56: 306

Tjeerdsma, B.F., Boonstra, M.; Pizzi, A., Tekely, P., Militz, H. (1998): Characterisation of thermally modified wood: molecular reasons for wood performance improvement. *Holz als Roh- und Werkstoff* 56: 149-153.

1997

Acker, J. van, Klaassen, R.K.W.M., Militz, H., Stevens, M. (1997): The development of blue stain in service in sapwood of European softwood species. International Research Group on Wood Preservation, Document WP 97 – 10236, Whistler, Canada.

Machek, L., Militz, H., Gard, W. (1997): The use of modulus of rupture and modulus of elasticity in natural durability testing. The International Research Group on Wood Preservation, Document IRG/WP 97-20117, Whistler, Canada

Militz, H., Beckers, E.P.J., Homan, W.J. (1997): Modification of solid wood: research and practical potential. The International Research Group on Wood Preservation, Document Nr. IRG/WP 97-40098, Whistler, Canada

Patente

Militz H, Mai C, Nguyen HM (2009) Schutzmittel für lignocellulosisches Material auf Basis von Fettsäure- und Paraffinderivaten. Veröffentlichungsnummer: EP1716995, Europäisches Patentamt.

Hydrophobierung von Holzprodukten für den Einsatz als Haushaltswaren, unter besonderer Berücksichtigung der verringerten Rissbildung und Spülmaschinentauglichkeit. Militz, H.; Treu, A.: DE 102005059207.4

Wiederverwendbare Messelektrode für Holzfeuchtemessgeräte auf Widerstandsbasis. Militz, H.; Bringemeier, B.: DE 202006016002.7

Herstellung von Formkörpern aus feinteiligen Materialien auf Basis von Lignocellulose. Militz, H.: DE/04.03.05/ DEA 102005010042

Verfahren zur Verbesserung der Oberflächenhärte eines Holzkörpers mit einer wässrigen Lösung eines Imprägniermittels. Militz, H.; Krause, A.: DE 102 46 400 A1 2004.08.05

Verfahren zur Verbesserung der Dauerhaftigkeit, Dimensionsstabilität und Oberflächenhärte eines Holzkörpers. Militz, H.; Krause, A.: DE 102 46 401 A1 2004.08.05

Verfahren zur Herstellung von Holzwerkstoffen. Militz, H.; et al.: DE 10 2005 010 041 A1 2006.09.07

- Verfahren zum Imprägnieren von Lignocellulosematerialien mit Effektstoffen. Miltz, H. et al.: DE 10 2006 019 816 A1 2006.11.09
- Verfahren zur Behandlung von Holzoberflächen. Miltz, H. et al.: DE 10 2006 019 817 A1 2006.11.09
- Verwendung wässriger Wachsdispersionen zur Imprägnierung von Lignocellulose-Materialien. Miltz, H. et al.: DE 10 2006 019 818 A1 2006.11.09
- Wässrige, härtbare Zusammensetzungen zum Imprägnieren von Lignocellulosematerialien. Miltz, H. et al.: DE 10 2006 019 819 A1 2006.11.09
- Verfahren zum Hydrophobieren von Lignocellulosematerialien. Miltz, H. et al. : DE 10 2006 019 820 A1 2006.11.09
- Verwendung von modifizierten Holzwerkmaterialien zur Herstellung von Gegenständen. Miltz, H. et al.: DE 10 2005 045 533 A1 2007.03.29
- Herstellung modifizierter Lignocellulosematerialien. Miltz, H. et al.: DE 10 2005 047 362 A1 2007.04.12
- Formaldehydarmes Lignocellulosematerial und Verfahren zu dessen Herstellung. Miltz, H. et al.: DE 10 2005 047 363 A1 2007.04.12
- Verfahren zur Herstellung modifizierter Furnierwerkstoffe. Miltz, H. et al.: DE 10 2005 061 998 A1 2007.07.05
- Silanisierung von Holzspänen und -fasern zur Herstellung von Holz-Plastik-Kompositwerkstoffen. Miltz, H. et al.: WO 2007/107551 A1 2007.09.27 DE 10 2006 013 090.1
(Silanization of wood turnings and fibers for producing wood-plastic composite materials)
- Kompositwerkstoff aus Holz und thermoplastischem Kunststoff. Miltz, H. et al.: DE 10 2006 013 090 A1 2007.09.27
- Mittel zur Ausstattung von auf Cellulose und/oder Stärke basierenden Substanzen mit Wasser abweisenden und gleichzeitig pilz-, bakterien-, insekten- sowie algenwidrigen Eigenschaften. Miltz, H., Mai, C. et al.: PCT / EP 2005 / 052560, Anmeldung 10 2004 037 044
- Schuttmittel und Vergütung für Holz. Miltz, H., Mai, C., Weigenand, O.: DE 10 2004 036 918
- Verwendung von Polymeren mit Amino- bzw. Ammoniumgruppen zur Erhöhung der Dauerhaftigkeit von Holz gegenüber holzbesiedelnden Pilzen. Miltz, H., Mai, C.: CPA-0677-SUG
- Schuttmittel für lignocellulosches Material auf Basis von Fettsäure- und Paraffinderivaten. Miltz, H., Mai, C.: CPA-0682-SUG
- Treatment and coating for wood. Miltz, H., Mai, C., Weigenand, O.: PCT/EP 2005/053399

Microwave curing of impregnated wood. Treu, A., Militz, H.: PCT WO 2008/140324 A1

2002

- Hapla, F.; Meggers, L.; Militz, H.; Mai, C. (2002): Investigation on the yield and quality of sliced veneers produced from beech trees (*Fagus sylvatica* L.) containing red heartwood. Holz als Roh- und Werkstoff 60: 440-442
- Militz, H. (2002): Heat treatment technologies in Europe: Scientific background and technological state-of-art. Proceedings of FPRS Conference „Enhancing durability of lumber and engineered wood products“, Florida, USA: 239-249
- Militz, H. (2002): Thermal treatment of wood: European processes and their background. International Research Group on Wood Preservation, Document 02-40241, 33rd Annual Meeting Cardiff, UK
- Militz, H. (2002): Solid wood modification. Proceedings Part 1, Cost E13 Int. Symposium on Wood Based Materials: Wood Composites and Chemistry. 19.-20.9.2002 Vienna, Austria, 1
- Militz, H. (2002): Modified wood. A new material for new and existing markets. Proceedings of 1st European Wood Conference “Wood industry in Europe-growing together”. Hamburg 10.10.2002: 69-74
- Mohebbi, B.; Militz, H. (2002): Soft rot decay in acetylated wood. Chemical and anatomical changes in decayed wood. International Research Group on Wood Preservation, Document 02-40231, 33rd Annual Meeting Cardiff, UK
- Stuber, B.; Militz, H.; Weihs, U.; Krummheuer, F. (2002): Nomenklatur und Physiologie der fakultativen Kernbildung von Rotbuche (*Fagus sylvatica* L.). Forst und Holz 57: 129-133

Tjeerdsma, B.F., Stevens, M., Militz, H., van Acker, J. (2002): Effect of process conditions on moisture content and decay resistance of hydro-thermally treated wood. *Holzforschung und -verwertung* 54, 5: 94-99

2001

de Meijer, M.; Militz, H. (2001): Moisture transport in coated wood. Part 2: Influence of coating type, film thickness, wood species, temperature and moisture gradient on kinetics of sorption and dimensional change. *Holz als Roh- und Werkstoff* 58: 467-475

de Meijer, M.; Thurich, K.; Militz, H. (2001): Quantitative measurements of capillary coating penetration in relation to wood and coating properties. *Holz als Roh- und Werkstoff* 59: 35-45

de Meijer, M.; Velde, B. van de; Militz, M. (2001): Rheological approach to the capillary penetration of coating into wood. *Journal of Coatings Technology* 73, 914: 39-51

Hapla, F.; Militz, H. (2001): On the importance of wood quality against the background of ecological silviculture. - Contemplation of relevant silvicultural mixed-stand systems. Proceedings of the 5th Workshop COST-Action E10 "Wood Properties for Industrial Uses", Hurdal, Norway

Machek, L.; Militz, H.; Sierra-Alvarez, R. (2001): The influence of wood moisture content on dynamic modulus of elasticity measurements in durability testing. *Holzforschung und -verwertung* 53, 5: 97-100

Machek, L.; Militz, H.; Sierra-Alvarez, R. (2001): The use of an acoustic technique to assess wood decay in laboratory soil-bed tests. *Wood Science and Technology* 34: 467-472

Militz, H. (2001): Oils and water repellents in wood preservation. Proceedings of a special seminar of COST E22, Reinbek 2001, 65 Seiten (Editor)

Rijckaert, V.; Stevens, M.; van Acker, J.; de Meijer, M.; Militz, H. (2001): Quantitative assessment of the penetration of water-borne and solvent-borne wood coatings in Scots pine sapwood. *Holz als Roh- und Werkstoff* 59: 278-287

Treu, A.; Militz, H.; Breyne, S. (2001): Royal-treatment - scientific background and practical application. European Conference of COST E22, Reinbek, Germany

van Ekeveld, A.; Homan, W.J.; Militz, H. (2001): Water repellency of some natural oils. European Conference of COST E 22, Reinbek, Germany

van Ekeveld, A.; Homan, W.J.; Militz, H. (2001): Increasing the water repellency of Scots pine sapwood. *Holzforschung und -verwertung* 53, 6: 113-115

2000

de Meijer, M.; Militz, H. (2000): Adhesion of low-VOC-coatings on wood: a quantitative analysis. *Progress in Organic Coatings* 28: 223-240

- de Meijer, M.; Militz, H. (2000): Moisture transport in coated wood. Part 1: Analysis of sorption rates and moisture content profiles in spruce during liquid water uptake. *Holz als Roh- und Werkstoff* 58: 354-362
- Militz, H.; Tjeerdsma, B. (2000): Heat treatment of wood by the "PLATO-Process". Proceedings of heat treatment conferences, Helsinki, Stockholm, Oslo
- Militz, H.; van Acker, J. (2000): Wood modification towards practical application. A european perspective. IUFRO World Conference, Kuala Lumpur, Malaysia
- Militz, H. (2000): Alternative Schutz- und Behandlungsverfahren. 22. Deutsche Holzschutz-Tagung, Bad Kissingen
- Militz, H.; Bloom, C.J. (2000): The use of lap-joints in natural durability testing: Moisture content development during 36 months outside exposure trials. International Research Group on Wood Preservation, Document WP 00-20217, Hawaii, USA
- Sundell, P.; de Meijer, M.; Militz, H. (2000): Preventing light induced degradation of wood by acetylation: A study on lignin and lignin model compounds. In: Second Wood Coatings Conference "Wood Coatings, Challenges and Solutions in the 21th Century, The Hague, The Netherlands
- Tjeerdsma, B.F.; Stevens, M.; Militz, H. (2000): Durability aspects of (hydro)thermal treated wood. International Research Group on Wood Preservation, Document WP 00-40160, Hawaii, USA

1999

- Acker, J. van, Militz, H., Stevens, M. (1999): The significance of accelerated laboratory testing methods for determining the natural durability of wood. *Holzforschung*: 449-458.
- Meijer, M. de, Militz, H. (1999): Sorption behaviour and dimensional changes of wood coatings composites. *Holzforschung*: 553-560.
- Meijer, M. de, Militz, M. (1999): Adhesion of low-VOC coatings on wood: a quantitative analysis. *Verfkroniek* 4: 25-30.
- Polman, J.E., Michon, S.G.L., Militz, H., Helmink, A.T.F. (1999): The wood of *Metasequoia glyptostroboides* (Hu en Cheng) of Dutch origin. *Holz als Roh und Werkstoff*: 215-221

1998

- Acker, J. van, Stevens, M., Carey, J., Sierra-Alvarez, R., Militz, H., Le Bayon, I., Kleist, G., Peek, R-D. (1998): Criteria for basidiomycete testing and ways of defining natural durability classes. The International Research Group on Wood Preservation, Document WP 98-20144, Maastricht, The Netherlands.
- Beckers, E.P.J., De Meijer, M., Militz, H., Stevens, M. (1998): Performance of finishes on wood that is chemically modified by acetylation. *Journal of Coatings Technology*. Vol. 70. No 878: 59-67.

Meijer, M. de, Thurich, K., Militz, H. (1998): Comparative study on penetration characteristics of modern wood coatings. *Wood Science and Technology*: 347-365.

Meijer, M. de, Militz, H. (1998): Wet adhesion measurements of wood coatings. *Holz als Roh- und Werkstoff* 56: 306

Tjeerdsma, B.F., Boonstra, M.; Pizzi, A., Tekely, P., Militz, H. (1998): Characterisation of thermally modified wood: molecular reasons for wood performance improvement. *Holz als Roh- und Werkstoff* 56: 149-153.

•

1997

Acker, J. van, Klaassen, R.K.W.M., Militz, H., Stevens, M. (1997): The development of blue stain in service in sapwood of European softwood species. International Research Group on Wood Preservation, Document WP 97 – 10236, Whistler, Canada.

Machek, L., Militz, H., Gard, W. (1997): The use of modulus of rupture and modulus of elasticity in natural durability testing. The International Research Group on Wood Preservation, Document IRG/WP 97-20117, Whistler, Canada

Militz, H., Beckers, E.P.J., Homan, W.J. (1997): Modification of solid wood: research and practical potential. The International Research Group on Wood Preservation, Document Nr. IRG/WP 97-40098, Whistler, Canada

Patente

Hydrophobierung von Holzprodukten für den Einsatz als Haushaltswaren, unter besonderer Berücksichtigung der verringerten Rissbildung und Spülmaschinentauglichkeit. Militz, H.; Treu, A.: DE 102005059207.4

Wiederverwendbare Messelektrode für Holzfeuchtemessgeräte auf Widerstandsbasis. Militz, H.; Bringemeier, B.: DE 202006016002.7

Herstellung von Formkörpern aus feinteiligen Materialien auf Basis von Lignocellulose. Militz, H.: DE/04.03.05/ DEA 102005010042

Verfahren zur Verbesserung der Oberflächenhärte eines Holzkörpers mit einer wässrigen Lösung eines Imprägniermittels. Militz, H.; Krause, A.: DE 102 46 400 A1 2004.08.05

Verfahren zur Verbesserung der Dauerhaftigkeit, Dimensionsstabilität und Oberflächenhärte eines Holzkörpers. Militz, H.; Krause, A.: DE 102 46 401 A1 2004.08.05

Verfahren zur Herstellung von Holzwerkstoffen. Militz, H.; et al.: DE 10 2005 010 041 A1 2006.09.07

Verfahren zum Imprägnieren von Lignocellulosematerialien mit Effektstoffen. Militz, H. et al.: DE 10 2006 019 816 A1 2006.11.09

Verfahren zur Behandlung von Holzoberflächen. Militz, H. et al.: DE 10 2006 019 817 A1 2006.11.09

Verwendung wässriger Wachsdispersionen zur Imprägnierung von Lignocellulosematerialien. Militz, H. et al.: DE 10 2006 019 818 A1 2006.11.09

Wässrige, härtbare Zusammensetzungen zum Imprägnieren von Lignocellulosematerialien. Militz, H. et al.: DE 10 2006 019 819 A1 2006.11.09

Verfahren zum Hydrophobieren von Lignocellulosematerialien. Militz, H. et al. : DE 10 2006 019 820 A1 2006.11.09

Verwendung von modifizierten Holzwerkmaterialien zur Herstellung von Gegenständen. Militz, H. et al.: DE 10 2005 045 533 A1 2007.03.29

Herstellung modifizierter Lignocellulosematerialien. Militz, H. et al.: DE 10 2005 047 362 A1 2007.04.12

Formaldehydarmes Lignocellulosematerial und Verfahren zu dessen Herstellung. Militz, H. et al.: DE 10 2005 047 363 A1 2007.04.12

Verfahren zur Herstellung modifizierter Furnierwerkstoffe. Militz, H. et al.: DE 10 2005 061 998 A1 2007.07.05

Silanisierung von Holzspänen und -fasern zur Herstellung von Holz-Plastik-Kompositwerkstoffen. Militz, H. et al.: WO 2007/107551 A1 2007.09.27 DE 10 2006 013 090.1

(Silanization of wood turnings and fibers for producing wood-plastic composite materials)

Kompositwerkstoff aus Holz und thermoplastischem Kunststoff. Miltz, H. et al.: DE 10 2006 013 090 A1 2007.09.27

Mittel zur Ausstattung von auf Cellulose und/oder Stärke basierenden Substanzen mit Wasser abweisenden und gleichzeitig pilz-, bakterien-, insekten- sowie algenwidrigen Eigenschaften. Miltz, H., Mai, C. et al.: PCT / EP 2005 / 052560, Anmeldung 10 2004 037 044

Schutzmittel und Vergütung für Holz. Miltz, H., Mai, C., Weigenand, O.: DE 10 2004 036 918

Verwendung von Polymeren mit Amino- bzw. Ammoniumgruppen zur Erhöhung der Dauerhaftigkeit von Holz gegenüber holzbesiedelnden Pilzen. Miltz, H., Mai, C.: CPA-0677-SUG

Schutzmittel für lignocellulosisches Material auf Basis von Fettsäure- und Paraffinderivaten. Miltz, H., Mai, C.: CPA-0682-SUG

Treatment and coating for wood. Miltz, H., Mai, C., Weigenand, O.: PCT/EP 2005/053399

Microwave curing of impregnated wood. Treu, A., Miltz, H.: PCT WO 2008/140324 A1